

PANEL

Tamaño de pantalla	75 "
Tecnología de panel	IPS
Resolucion nativa	3.840 × 2.160 (UHD)
Brillo (típico, cd / m²)	500
Relación de contraste	1.000:1
CR dinámico	1,000,000: 1 * La relación de luminosidad del color Full Black / Full White en la condición de entrada de video.
Gama de colores	NTSC 72%
Ángulo de visión (H x V)	178 x 178
Profundidad del color	1.07 mil millones de colores (10 bits)
Tiempo de respuesta	6 ms (G a G)
Tratamiento de superficies	Neblina 28%
Horas de funcionamiento (horas / día)	24/7
Retrato / paisaje	Sí Sí

CONECTIVIDAD

Aporte	HDMI (2, HDCP 2.2/1.4), HDMI (1, HDCP 1.4), DP (1, HDCP 2.2/1.3), DVI-D (HDCP 1.4), Audio, USB 2.0 Type A (2)
Output	DP, Audio
External Control	RS232C (4 Pin Phone Jack) In / Out, RJ45(LAN) In, IR In

MECHANICAL SPECIFICATION

Bezel Color	Black
Bezel Width	14.9 mm (Even Bezel)
Weight (Head)	41.5 kg
Monitor Dimension (W × H × D)	1,682.4 × 960.3 × 57.9 mm (Without Handle and LG Logo)
Handle	Yes
VESA™ Standard Mount Interface	600 x 400 mm

SPECIAL FEATURE

Overlay Touch Compatibility	No
-----------------------------	----

ENVIRONMENT CONDITIONS

Operation Temperature	0°C to 40°C
Operation Humidity	10 % to 80 %

POWER

Power Supply	AC 100–240 V ~, 50/60 Hz
Power Type	Built-In Power

POWER CONSUMPTION

Typ./Max	180 W / 260 W
BTU (British Thermal Unit)	614.25 BTU/Hr(Typ.), 887.25 BTU/Hr(Max)

SOUND

Speaker	Yes
---------	-----

CERTIFICATION

Safety	CB / NRTL
EMC	FCC Class "A" / CE / KC
ErP	Yes

OPS COMPATIBILITY

OPS Type Compatible	Yes
OPS Power Built In	Yes

SOFTWARE COMPATIBILITY

SuperSign CMS	Yes
SuperSign Control / Control+	Yes
SuperSign WB	Yes
SuperSign Media Editor	Yes

ACCESSORY

Basic	Remote Controller, Power Cord, QSG, DP Cable (1.8 M), Regulation Book, Phone to RS232C Gender
Optional	OPS Kit (KT-OPSF) LSW640A/B (Wall Mount), Touch overlay (KT-T75E)