



The Professional's Source Since 1973

420 9th Ave. at 34th St. in New York City
www.bhphotovideo.com

Sales: 212.444.6615
Customer Service: 212.239.7765

Hikvision DS-2CD2043G0-I 4MP Outdoor Network Bullet Camera with Night Vision & 2.8mm Lens (White)

BH #HID2043G0I28 • MFR #DS-2CD2043G0-I 2.8MM

HIKVISION
Distribuidor Autorizado



En Stock

Atención Clientes Internacionales

No garantizamos la exactitud de ninguna información en moneda extranjera. [Más Detalles](#)

Key Features

- 2688 x 1520 Resolution at 30 fps
- IR LEDs for Night Vision up to 100'
- 2.8mm Fixed Lens
- 103° Horizontal Field of View
- microSD Slot Supports up to 128GB
- RJ45 Ethernet with PoE Technology
- Complies with ONVIF Profiles S & G
- IP67 Rated for Outdoor Use

En la Caja n

Hikvision DS-2CD2043G0-I 4MP Outdoor Network Bullet Camera with Night Vision & 2.8mm Lens (White)

Limited 3-Year Warranty

Hikvision DS-2CD2043G0-I Specs

Camera

Sensor 4 MP 1/3" CMOS

Lens Mount **Press  for Accessibility menu n people**

Focal Length 2.8mm

Maximum Aperture	f/1.6
Lens Field of View	Horizontal: 103° Vertical: 58° Diagonal: 123°
IR Cut Filter	Mechanical
Day/Night	Yes
Minimum Illumination	Color: 0.018 Lux B&W: 0 Lux
Shutter Speed	1/100,000 to 1/3 Seconds

Video

Streaming Resolution	2688 x 1520 at 30 fps (16 Mb/s)
Supported Video Compression	H.264, H.264+, H.265, H.265+, MJPEG
Multi-View Streaming	Yes, 3 Streams
Automatic Gain Control	Yes

Networking

Security	HTTPS, IEEE 802.1X, IP Address Filtering, Password Protection, Watermark
Supported Protocols	Bonjour, DDNS, DHCP, DNS, FTP, HTTP, ICMP, IGMP, IPv4/v6, NTP, PPPoE, QoS Layer 3 DiffServ, RTCP, RTP, RTSP, SMTP, SNMP v1/v2c/v3 (MIB-II), TCP, UDP, UPnP

System Integration

Application Program Interface (API) **Press  for Accessibility menu n people**

Analytics	Motion Detection Line Crossing Detection
-----------	---

Intrusion Detection
Exception Detection

Event Trigger	Yes
Event Action	Recording, Notification, Alarm
Data Streaming	Yes

System Requirements

Mobile Operating Systems	iOS, Android
--------------------------	--------------

Environmental

Operating Temperature	-22 to 140°F / -30 to 60°C
Operating Humidity	0 to 95%
IP Rating	IP67

General

Media/Memory Card Slot	Single Slot: microSD/microSDHC/microSDXC [128 GB Maximum]
Pan/Tilt	None
I/O Connections	1 x RJ45 1 x Power
IR Illuminators	850 nm
IR Range	100' / 30.48 m
Video Management Software	iVMS-4200, Hik-Connect
Internal Storage	None
External Storage Options	NAS

Press  **for Accessibility menu**  **people**

Power Source	DC, PoE 802.3af (15 W)
Power Consumption	DC: 6 W PoE: 7.5 W
Material of Construction	Metal (Unspecified Type)
Dimensions	ø: 2.8 x L: 6.1" / ø: 70.0 x L: 155.0 mm
Weight	0.9 lb / 0.41 kg

Packaging Info

Package Weight	1.35 lb
Box Dimensions (LxWxH)	8.6 x 4.9 x 4.6"