



C-HM/HM/ETH

Cable HDMI Alta Velocidad con Ethernet

| HDMI | 4K/60 UHD (4:2:0) | 4K/60 UHD (4:4:4)



El cable Kramer C-HM/HM/ETH es un cable de altas prestaciones acabado con conectores HDMI en ambos extremos. Soporta Canal Ethernet, Profundidad de Color, x.v.Color™, Lip Sync, 7.1 PCM, Dolby TrueHD, DTS-HD, CEC y ARC y resoluciones hasta 4K@60Hz (4:4:4)

FEATURES

Rendimiento de Calidad - Los cables Kramer de HDMI proporcionan una conexión digital sin compresión entre el equipamiento electrónico de consumo tales como reproductores DVD, decodificadores y monitores audio/vídeo tales como pantallas de plasma para TV de alta definición

Máx. Resolución - 4K@60Hz (4:4:4)

Conectores de Alta Calidad - Conectores dorados de 24k para resistir la corrosión, y ofrecer la mejor conectividad posible

Conectores K-Lock Resistentes a la Extracción - Proporciona una fuerza de restricción de 15 libras para una conexión sin deslizamiento

Variada Selección de Longitudes - Disponible en versiones de 0.9 a 15.2m (3,6,10,15,25,35 y 50 pies)



TECHNICAL SPECIFICATIONS

Video	Max Resolution for 3–15ft (.9–4.6m) lengths: 4K@60Hz (4:4:4) Max Resolution for 25–35ft (7.6–10.7m) lengths: 4K@60Hz (4:2:0) Max Resolution for 50ft (15.2m) lengths: 1080p Max Data Rate for 3–15ft (.9–4.6m) lengths: 18 Gbps (6Gbps per channel) Max Data Rate for 25–35ft (7.6–10.7m) : 10.2 Gbps (3.4Gbps per channel) Max Data Rate for 50ft (15.2m) lengths: 4.95Gbps (.99Gbps per channel) Supported Color Spaces: RGB, YCbCr, xvYCC, Adobe sRGB, sYCC601, BT.2020 HDMI Compliance: HDR, HDCP 2.2, EDID and CEC, ARC and ETH
Amplifier	Supported Audio Formats: Dolby Digital Plus™, Dolby TrueHD™, DTS–HD Master Audio™, DVD Audio, SA–CD
PHYSICAL	HDMI Source: On a male HDMI type A, 24K gold–plated K–Lock connector HDMI Display: On a male HDMI type A, 24K gold–plated K–Lock connector
CONDUCTORS	Material: Tinned Copper 3–35ft (.9–10.7m) lengths: 28AWG (7/0.127) 50ft (15.2m) lengths: 26AWG (7/0.160)
SCREENING	Type: Triple shielding
JACKET	Material: PVC Color: Gray Diameter for 3–35ft (.9–10.7m) lengths: 7.30 ± 0.20mm Diameter for 50ft (15.2m) lengths: 8.50 ± 0.20mm
MECHANICAL	Cable Bending Radius for 3–35ft (.9–10.7m) lengths: 73mm Cable Bending Radius for 50ft (15.2m) lengths: 85mm
ELÉCTRICA	Temperature Rating: 80°C Voltage Rating: 30V Conductor Resistance – 28AWG: 239.0Ω/km Conductor Resistance – 26AWG: 150Ω/km MAX. at 20Ω
STANDARDS COMPLIANCE	Safety: Flammability Rating – CL3/FT4 Environmental: RoHS 2011/65/ EU





CONFIGURATIONS

C-HM/HM/ETH-3	Cable HDMI (M) a HDMI (M) con Ethernet
C-HM/HM/ETH-6	Cable HDMI (M) a HDMI (M) con Ethernet
C-HM/HM/ETH-10	Cable HDMI (M) a HDMI (M) con Ethernet
C-HM/HM/ETH-15	Cable HDMI (M) a HDMI (M) con Ethernet
C-HM/HM/ETH-25	Cable HDMI (M) a HDMI (M) con Ethernet
C-HM/HM/ETH-35	Cable HDMI (M) a HDMI (M) con Ethernet
C-HM/HM/ETH-50	Cable HDMI (M) a HDMI (M) con Ethernet