

# CEN-SW-POE-5

## 5-Port PoE Switch

- > 5-port unmanaged Ethernet switch
- > All ports support 1000Base-T Gigabit Ethernet
- > Provides PoE (802.3af) on 4 ports
- > Auto-negotiating and auto MDI/MDIX
- > Rugged metal enclosure
- > Surface or rack-rail mountable

The CEN-SW-POE-5 is a 5-port unmanaged Gigabit Ethernet switch that provides Power over Ethernet (PoE) from four of its ports. Power over Ethernet affords a one-wire solution for connecting Crestron touch screens, gateways, and other devices, delivering power and data over a single CAT5/6 network cable. All 5 ports are Gigabit capable to ensure maximum bandwidth for multimedia and critical control data.

Using the CEN-SW-POE-5, there is no need to install a separate power supply at each networked device location. The CEN-SW-POE-5 can simply be mounted at a convenient location on a wall or in an equipment rack, providing a single power source for four separate 802.3af compliant PoE powered devices. Non-PoE devices may also be connected to any port on the CEN-SW-POE-5 without risk of damage to either component.



## SPECIFICATIONS

### Ethernet

**Ports:** (5) 10Base-T/100Base-TX/1000Base-T Ethernet  
**Network Standards:** IEEE 802.3, 802.3u, 802.3ab, 802.3x, & 802.3af  
**Transmission Method:** Store-and-Forward

### Indicators

**PoE 1 – 4:** (4) green LEDs, indicate a PoE powered device is connected to each corresponding Ethernet port

**Uplink:** (1) green LED and (1) amber LED; indicate Ethernet link status, speed, and activity at the Uplink port

**1 – 4:** (1) green LED and (1) amber LED per each of (4) Ethernet ports; indicate Ethernet link status, speed, and activity at each corresponding port

**Power:** (1) yellow LED, indicates operating power supplied via external power pack

### Connectors

**Uplink:** (1) 8-wire RJ45, female;  
10Base-T/100Base-TX/1000Base-T Ethernet port

**1 – 4:** (4) 8-wire RJ45, female;  
10Base-T/100Base-TX/1000Base-T Ethernet ports and PoE Power Sourcing Equipment (PSE) outputs

**G:** (1) 6-32 screw, chassis ground lug

**48VDC:** (1) 4-pin (2x2) rectangular connector;  
48 Volt DC power input (power pack included)

### Power Requirements

**Power Pack:** 1.25 Amps @ 48 Volts DC;  
100-240 Volts AC 50/60 Hz power pack included

### Environmental

**Temperature:** 32° to 104°F (0° to 40°C)  
**Humidity:** 10% to 90% RH (non-condensing)  
**Heat Dissipation:** 10 BTU/hour

### Enclosure

**Chassis:** Metal, black finish, with (2) integral mounting flanges, vented top and bottom  
**Mounting:** Freestanding, surface mount, or attach to a single rack rail

### Dimensions

**Height:** 5.06 in (129 mm)  
**Width:** 4.66 in (119 mm)  
**Depth:** 1.17 in (30 mm)

### Weight

13.5 oz (381 g)

# CEN-SW-POE-5 5-Port PoE Switch

## MODELS & ACCESSORIES

### Available Models

#### CEN-SW-POE-5: 5-Port PoE Switch

#### Notes:

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.

