

## PTZOptics

Introducing the new SuperJoy Joystick Controller supporting Network and Serial Camera Control. Experience the full capabilities by pairing it with PTZOptics or HuddleCamHD cameras.

### Main Features

- Durable metal housing
- PTZOptics VISCA over IP & Serial control
- Limited NDI & Sony control
- PTZOptics Camera On Screen Display control
- Full Pan / Tilt / Zoom camera control
- PTZ, Focus, and Preset Speed Adjustment on the fly
- 5 Camera Control Groups
  - Groups 1-4 limited to 7 cameras
- 255 camera presets, 9 Quick presets
- 4 Customizable buttons (TCP, UDP, & HTTP)
- Fine tune zoom & focus control dials
- Buttons glow / flash when available
- RTSP Decoder via HDMI
- PTZOptics Focus Lock & Unlock
- Large LCD screen with controller status
- Import / Export settings via network & USB
- 2-Year warranty

### Model Number: PT-SUPERJOY-G1

**What's in the box?**

- PT-SUPERJOY-G1 Joystick Controller
- 12V 2A DC International Power Supply
- RS-232C | DB9 to 8-pin mini-din cable
- PT-SUPERJOY-G1 Quick Start Guide
- Grounding Pin



Technical Specifications	
Connections	RS-232, RS-485, RS-422, RJ-45
Control Protocols	VISCA, VISCA over IP, PELCO-D, PELCO-P, Sony, & NDI
Max Cameras	253 cameras total (Cam Groups 1-4: 7 channels Cam Group 5: 225 channels)
Recommended Max Distance	RS-232 / RS-422: 50 ft   15m RS-485: 3,937 ft   1200m Ethernet: 328 ft   100m
Baud rate	1200 ~ 19200 bps

Operation Specifications	
Power	6W   12VDC / PoE (802.3af) (Only use one (1) power source at a time.)
Working Temp	14° F ~ 122° F   -10° C ~ +50° C
Working Humidity	10% ~ 90% (non-condensation)
Weight	3.75 lbs   1.70 kg
Dimensions (in.)	13.94 W x 7.05 D x 3.98 H
Dimensions (mm.)	370 W x 180 D x 101 H