

# HD-CONV-USB-300

## USB Converter with HDMI® and Analog Audio Input



- *Converts a 4K60 4:4:4 HDMI® input to a USB 3.0 output*
- *Captures uncompressed 1080p60 video and stereo audio over USB 3.0<sup>1</sup>*
- *Supports deep-color and HDR up to 12-bit*
- *HDCP 2.2 and HDCP 1.x compliant on HDMI input and output<sup>2</sup>*
- *Automatically downscales 4K sources to 1080p for USB capture*
- *Supports capturing 2-channel digital audio from either HDMI (LPCM 2.0) or the 3.5 mm analog audio input*
- *Compliant with the USB Audio Class (UAC) and USB Video Class (UVC) standards*
- *HDMI output port for local viewing or loop-through functionality*
- *Compact surface-mountable housing*

The Crestron HD-CONV-USB-300 converts an HDMI® signal to USB 3.0. The device captures uncompressed 1080p60 video with stereo digital or analog audio. USB capture is accomplished using the USB Video Class (UVC) and USB Audio Class (UAC) standards, which are compatible with the most common video capture or streaming software applications. Input resolutions larger than Full HD and up to 4K UHD are automatically scaled to 1080p for USB capture. Video timing stabilization helps to ensure a reliable and stable USB capture stream.

The HD-CONV-USB-300 can be used for stand-alone video conversion or as part of an integrated UC (unified communications) solution. By using the HDMI output and analog audio input, you can leverage existing video conferencing equipment in the room. For example, if you need to install a secondary UC codec to an existing installation, you can share the microphone and HDMI camera devices by feeding these signals into the HD-CONV-USB-300. The HDMI output can connect the camera signal back to the existing UC codec while the captured USB stream feeds into the new UC codec.

You can also install this device in an existing video conferencing room to add BYOM (Bring Your Own Meeting) capability. Simply connect the room's microphone and HDMI camera to the HD-CONV-USB-300 and connect via USB to the user's laptop to start the meeting from a soft codec while using the room's superior camera and microphone.

# HD-CONV-USB-300

## USB Converter with HDMI® and Analog Audio Input

### Specifications

#### Video

<b>Input Signal Type</b>	HDMI 2.0 (DVI 1.0 compatible)
<b>Output Signal Type</b>	USB 3.0 supporting UVC; <sup>1,2</sup> HDMI 2.0 (DVI 1.0 compatible) loop out port with support for HDCP 2.2/1.x
<b>Input Resolution</b>	4K UHD @ 60 fps 4:4:4 with support for 12-bit HDR
<b>Output Resolution</b>	USB: HD 1080p @ 60 fps uncompressed; HDMI: 4K UHD @ 60 fps 4:4:4 with support for 12-bit HDR

#### Audio

<b>Input Signal Type</b>	HDMI or analog audio input (selectable in configuration software)
<b>Output Signal Type</b>	USB 3.0 supporting UAC
<b>Format</b>	Stereo 2-channel LPCM

#### Communications

<b>USB</b>	USB 3.0 device supporting UVC and UAC
------------	---------------------------------------

#### Connectors

<b>HDMI IN</b>	(1) HDMI Type A connector, female; Digital video/audio input
<b>HDMI OUT</b>	(1) HDMI Type A connector, female; Digital video/audio output
<b>AUDIO IN</b>	(1) 3.5 mm analog audio input jack
<b>USB</b>	(1) USB 3.0 Type-B connector, female; USB 3.0 device port; USB 3.0 Type-B male to Type-A male cable included

#### Indicators

<b>PWR</b>	(1) LED Green indicates that there is an HDMI source. Red indicates that there is no HDMI source.
<b>ACTIVE</b>	(1) LED Green indicates that the software on the connected PC is actively receiving video from the unit via USB.
<b>HDCP</b>	(1) LED Red indicates that the source is using HDCP 1.x. Blue indicates that the source is using HDCP 2.2. Off indicates that the source is not using HDCP.

#### Power

USB powered

#### Environmental

<b>Temperature</b>	32° to 104° F (0° to 40° C)
<b>Humidity</b>	10% to 90% RH (non-condensing)

#### Construction

<b>Housing</b>	Metal (steel), black
<b>Mounting</b>	Freestanding, surface mountable, or attachment to a rack rail

#### Dimensions

<b>Height</b>	4.55 in. (116 mm)
<b>Width</b>	5.04 in. (128 mm)
<b>Depth</b>	0.98 in. (25 mm)

#### Weight

0.77 lb (0.349 kg)

#### Compliance

**Regulatory Model: M202118001**

UL® Listed for US and Canada, IC, CE, FCC Part 15 Class B digital device

#### Model

**HD-CONV-USB-300**

USB Converter with HDMI® and Analog Audio Input

#### Notes:

1. Compatible with USB 2.0 capture, but minimal MJPEG compression is applied. Note that a Y-cable (not included) is required when connected via USB 2.0 to deliver the necessary power.
2. HDCP encrypted sources cannot be converted to USB. HDCP content can be displayed on the HDMI output only.

# HD-CONV-USB-300

## USB Converter with HDMI® and Analog Audio Input

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/How-To-Buy/Find-a-Representative](http://www.crestron.com/How-To-Buy/Find-a-Representative) or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to [www.crestron.com/warranty](http://www.crestron.com/warranty) for full details.

The specific patents that cover Crestron products are listed online at [patents.crestron.com](http://patents.crestron.com).

Certain Crestron products contain open source software. For specific information, please visit [www.crestron.com/opensource](http://www.crestron.com/opensource).

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. HDMI and the HDMI logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. UL is either a trademark or registered trademark of Underwriters Laboratories, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2021 Crestron Electronics, Inc.

### HDMI

Specifications are subject to change without notice.  
©2021 Crestron Electronics, Inc.  
Rev 09/20/21

# HD-CONV-USB-300

USB Converter with HDMI® and Analog Audio Input

