

## Specifications

### PS 125

## General

Power output..... 12 VDC, regulated; 5 A maximum; 60 watts, total for all 8 outputs

**NOTE:** Maximum output current is rated at an ambient temperature of 40 °C.

Power input .....	100 VAC to 240 VAC, 50-60 Hz
No load .....	0.13 watts at 115 VAC 0.17 watts at 230 VAC
Full power.....	66.72 watts at 115 VAC 65.86 watts at 230 VAC
Temperature/humidity .....	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling .....	Convection, no vents
Thermal dissipation .....	34.4 BTU/hr
Mounting	
Rack mount.....	Yes, with optional 1U rack shelf
Furniture mount.....	Yes, with optional under-desk mounting kit
Enclosure type .....	Metal
Enclosure dimensions .....	1.75" H x 4.3" W x 8.5" D (1U high, quarter rack wide) (4.4 cm H x 11.0 cm W x 21.6 cm D) (Depth excludes connectors.)
Product weight .....	1.2 lbs (0.5 kg)
Regulatory compliance.....	CE, c-UL, PSE, UL, CISPR 22 Class B, C-tick, EN55022 Class B, FCC Class B, ICES Class B, VCCI Class B, Complies with the appropriate requirements of RoHS, WEEE
Product warranty .....	7 years parts and labor

**NOTE:** All nominal levels are at  $\pm 10\%$ .

**NOTE:** Specifications are subject to change without notice.

**NOTE:** Shipping weights and dimensions are available at [www.extron.com](http://www.extron.com).

5147-D1