

MB8-2PT-KIT

Kit with 2 x Mylo Bi-Color Half x 1 LED Light

ONE SHEET

Overview

Ikan's Mylo LED Light offers a wide variety of lighting options within a compact package for cinematographers. The high 95+ CRI LED lenses provide high color fidelity with a consistent brightness across all color temperatures! Its 3200-5600K Bi-Color Adjustability works well for any lighting scenario! The 50-degree beam angle makes it easy to light a large area with just one fixture. The Mylo MB8 Bi-Color LED Half x 1 light is equivalent to a 750-watt incandescent light.

Durability and versatility are key features of this impressive LED light. The heavy duty metal chassis allows it to endure any harsh field environment while the strong, steel tension knobs on the yoke securely lock the light in place at all times. The Baby 5/8" and Junior 1 1/8" combo pin also allow you to attach or configure it in different ways. As for battery power, an AC power supply and two Sony "L" series batteries for DC power come with this incredible light package!

On the back, the large yellow button/knob allows you to adjust the light's brightness and color temperature with a few simple clicks. Ikan's reliable barn doors with intensifiers are included to shape the light as needed. The LED readout also provides very precise measurements. With a maximum power draw of 50W at 120V, the new Mylo MB8 Bi-Color LED Half x 1 light can plug into any AC Power.



MB8-2PT-KIT | Kit with 2 x Mylo Bi-Color Half x 1 LED Light | UPC Code: 847983019663

Special Features

- 95+ CRI LEDs
- Bi-Color Adjustable from 3200K-5600K
- Bright consistent light across color temperatures
- 50° Beam Angle
- Baby 5/8 Inch and Junior 1-1/8 Inch Combo Pin adapter with right angle receiver hole
- Strong Steel tension knobs for locking the light into place
- Heavy Duty metal chassis
- Single knob control for adjusting color or brightness.

Recommended For

- Studio Lighting
- Field Lighting

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

MB8-2PT-KIT

95+ CRI LEDs

With more than 800 95+ LED lenses, the Mylo MB8 Light provides incredible color rendition and brightness.

Bi-Color Adjustability

The Mylo MB8 LED Light features a Bi-Color adjustable range between 3200K-5600K.

Consistently Bright

Consistent, bright lighting across all color temperatures is what you can expect from the Mylo MB8 Bi-Color Half x 1 LED Light.

50° Angle

A tight, 50° beam angle offers bright lighting for both short and long distances.

Combo Pin Adapter

The Baby 5/8 Inch and Junior 1-1/8 Inch combo pin includes a right angle receiver hole to quickly and easily attach it to any grip stand.

Steel Tension Knobs

The new, stronger steel tension knobs securely lock the light in place at any angle.

Reliable Durability

The heavy duty metal chassis enables you to use the light in any shooting environment without risk of damage.

Single Knob Control

A single knob control makes it easy to adjust the light's brightness & color temperature with a few simple clicks!

New LED Readout

The new LED readout is brighter and provides a quick reference of the light output with precise measurements.

Battery Options

An AC power supply and two Sony "L" batteries for DC power are included in this incredible package.

Barn doors Included

Ikan's reliable barn doors with intensifiers allow you to shape the light to suit your needs.

Maximum Power Draw

These lights output a maximum power draw of 50-Watts at 120 volts, allowing you to plug it into any AC power.

Incandescent Equivalent

The Mylo Bi-Color Half x 1 LED Light is equivalent to a 750-watt incandescent light.

Features you need, Prices you want.

MB8 Fixture Specifications

Light Source	800 0.06 Watt LEDs
Head Type	Bi-Color 3200K-5600K
Lens	45°
Beam Angle	50°
Control/Dimming	Knob Control
Build Material	Heavy Duty Metal Construction
Cooling System	Passive Cooling
Yoke	Baby 5/8" & Junior 1-1/8" Combo Pin
Fixture Size	14 x 7 x 2 In.
Fixture Weight	6 lbs

Power Specifications

Power Supply	Input: 100-240 VAC Output: 15VDC @5.0A
Fixture Power Consumption	24W; 7.4-14.8 VDC

Shipping Specifications

Shipping Dimensions	24 x 22 x 18 in.
Shipping Weight	38 lbs

What's Included

- 2 x Dual Charger with Power Supply
- 2 x Neutral Diffusion Filter
- 4 x Sony Style "L" Type Batteries
- 2 x Half x 1 Light Fixture
- 2 x Power Supply with Cable
- 2 x Yoke Mount
- 2 x Stands
- 1 x Stand Bag
- 1 x Light Bag

Accessories

- CV600 Digital LED Light Meter with Exposure & Spectrometer
- HD-STND Heavy Duty Light Stand
- KCP-703 Stage Clamp with 16mm Stud
- ROLLR-STND10 2-Stage Roller Stand 10' 6"
- SW-04 Safety Wire

