# IV-CAMPTZ-20-SLVR-1B

## 1 Beyond PTZ Intelligent Camera, 20x Optical Zoom, Silver



## Multicamera Capability with Automate Systems

Add the IV-CAMPTZ-20-SLVR-1B camera to an Automate multicamera system. Automate can be set to autoswitch between multiple 1 Beyond cameras to focus on the active speaking participant. Incorporate popular microphones and DSPs to switch between the presenter and audience.

#### Mounting Options

Standard mounting holes make it easy to mount the camera to a wall mount (included). Image flip allows the camera to be mounted inverted if needed.

- High quality video supporting resolutions up to 1080p60
- Control using VISCA over IP
- Smooth and quiet operation
- Compatible with Automate<sup>™</sup> multicamera systems
- Image Flip allows for optional inverted mounting
- Single Ethernet connection provides power (PoE+), monitoring, and control

The IV-CAMPTZ-20-SLVR-1B¹ is a high quality PTZ camera that can output up to 1080p60 resolution video via the 3G-SDI or HDMI® ports. It is ideal for any meeting where one camera needs to capture several areas of the room. The IV-CAMPTZ-20-SLVR-1B camera supports a single Ethernet connection and provides power (PoE+), monitoring, and control.

## **High Quality Video**

A high quality Sony Exmor CMOS sensor enables the camera to output up to 1080p60 resolution video via the 3G-SDI or HDMI ports.

### **Manual Control Options**

Use VISCA over IP to control the camera with a Crestron® control system. 1B Cam Manager Software is included for easy configuration from a computer on the network.

## Quiet, Fast Switching Between Presets

Up to 256 pan, tilt, and zoom combination presets can be configured. The camera will move to the selected preset point. A quiet, fast motor (120°/s pan speed) sets camera angles quickly.

# **IV-CAMPTZ-20-SLVR-1B**

# 1 Beyond PTZ Intelligent Camera, 20x Optical Zoom, Silver

# **Specifications**

## **Optics and Processing**

**Image Sensor** 1/2.8 in. Sony Exmor CMOS, 2.14MP

Focal Lens & f=4.7-94 mm, F1.6 - F3.5

Field of View 59.5° - 2.9°

Focus System Auto, Manual, PTZ Trigger, One Push

Minimum 0.5 Lux (30FPS)

Illumination

**Shutter Speed** 1/1 - 1/10,000 sec Gain Auto, Manual

White Balance Auto, Indoor, Outdoor, One Push, Manual Exposure Auto, Manual, Shutter Priority, Iris Priority

Number of Presets

Up to 256

Serial Control

RS-485, RS-232 (VISCA, PELCO-D)

IP Control Protocol

HTTP, RTP, TCP, UDP, ONVIF

## Pan, Tilt, Zoom

Tilt/Pan Angle Tilt: 30° - 90°, Pan: 170° - 170° **Tilt/Pan Speed** Tilt: 0.1° - 90° /s, Pan: 0.1° - 120° /s

Zoom 20x Optical, 20x Digital

## Connectivity

Ethernet RJ-45, 100Mb

#### Video

Video 3G-SDI, HDMI

Outputs1

1080p60/50/30/25, 1080i60/50, Signal

720p60/50/30/25 Formats (HD) IP Video H.264 (Dual stream)

Compression

Streaming RTSP, RTMP

Streaming Up to 1080p30, User-selectable Resolution framesize/framerate/bitrate

#### Audio

IP Audio AAC

Compression

Audio Input 1x Line In

#### **Power**

Power 12VDC, <30 W, PoE+

PoE+ Rating 25.5 W

#### **Environmental**

**Temperature** 32° to 104°F (0° to 40°C)

#### Construction

Mounting 1/4 in. threaded mount hole, compatible with

Wall Mount and J-Mount ceiling bracket

Color Silver S/N ≥50dB

#### **Dimensions**

**Dimensions** 8.9 in. x 8.1 in. x 6.3 in. (226 mm × 206 mm ×

160 mm)

#### Weight

3.74 lb (1.7 kg)

#### Note:

The IV-CAMPTZ-20-SLVR-1B camera includes integrated circuits produced by HiSilicon (part numbers HI3516ARBCV100 and HI3516ARFCV200), a subsidiary of Huawei Technologies Company.

## Included Accessories

**Power Supply** 

Wall Mount

Serial Control Breakout

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

This product is covered for a one-year warranty term under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full

The specific patents that cover Crestron products are listed online at

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. HDMI is either a trademark or a registered trademark of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

#### HDMI

Specifications are subject to change without notice.

©2022 Crestron Electronics, Inc.

Rev 05/19/22

