## Control Port Expansion Module

- > Fits within a 2-gang wall box behind the TPCS-4SM(D)
- > Provides 1 RS-232, 1 IR/serial, and 2 relay ports
- > Compatible with any Crestron® 2-Series or 3-Series™ control system
- > Interfaces via the Cresnet® control buss
- > 24 Volt DC Cresnet powered
- > Surface mount bracket included

The C2N-IO is a very compact device that adds control ports to any Crestron® 2-Series or 3-Series™ control system. It connects via the Cresnet® control network and provides one RS-232, one IR, and two relay control ports. It can be mounted to any flat surface using two screws or adhesive reclosable fastener (3M® Dual Lock® included).

The C2N-IO is ideally designed for use with a Crestron TPCS-4SM or TPCS-4SMD touch screen control system, providing an advanced wall mount control package that fits in a 2-gang US or UK electrical box. The C2N-IO can be mounted inside the electrical box behind the touch screen, or it can be installed remotely requiring just one Cresnet control cable for power and communications.

## **SPECIFICATIONS**

#### Communications

Cresnet®: Cresnet slave device, 2-Series and 3-Series™ compatible RS-232: Supports 2-way device control and monitoring up to 115.2k baud with software handshaking

IR/Serial: Supports 1-way device control via infrared up to 1.2 MHz or serial TTL/RS-232 (0-5 Volts) up to 115.2k baud

## Connectors

**RELAY 1 – 2:** (1) 4-pin captive screw terminal block comprising (2) normally open, isolated relays:

Rated 1 Amp, 30 Volts AC/DC;

Solid-state arc suppression across contacts

**COM:** (1) 3-pin captive screw terminal block, bidirectional RS-232 port; Up to 115.2k baud; software handshaking support

IR: (1) 2-pin captive screw terminal block, IR/Serial output port; IR output up to 1.2 MHz;

1-way serial TTL/RS-232 (0-5 Volts) up to 115.2k baud


NET: (2) 4-pin captive screw terminal blocks;

Cresnet slave ports, paralleled

## **Controls & Indicators**

**NET ID:** (2) rotary switches for manually setting Cresnet ID; '00' setting enables touch-settable ID (TSID)

PWR: (1) green LED, indicates operating power supplied via Cresnet control network



**NET:** (1) amber LED, indicates communication with Cresnet system **SETUP:** (1) red LED and (1) recessed miniature pushbutton for TSID

#### **Power Requirements**

Cresnet Power Usage: 1 Watt (42 mA @ 24 Volts DC)

## **Environmental**

Temperature: 32° to 104°F (0° to 40°C) Humidity: 10% to 90% RH (non-condensing)

Heat Dissipation: 3.5 BTU/Hr

#### **Enclosure**

Metal, freestanding or surface mount, surface mount bracket and 3M<sup>®</sup> Dual Lock<sup>®</sup> reclosable fastener included, fits inside a 2-gang electrical box or 2-gang UK (BS 4662) electrical box, 35 mm (1.38 in) minimum internal box depth required for C2N-IO and TPCS-4SM(D) combined

#### **Dimensions**

Height: 2.25 in (58 mm)

Width: 3.50 in (89 mm), 4.38 in (112 mm) with bracket

**Depth:** 0.83 in (21 mm)

## Weight

2.7 oz (75 g)



## **C2N-IO** Control Port Expansion Module

## **MODELS & ACCESSORIES**

## **Available Models**

C2N-IO: Control Port Expansion Module

## **Available Accessories**

IRP2: IR Emitter Probe w/Terminal Block Connector

CNSP-XX: Custom Serial Interface Cable

CRESNET-NP: Cresnet® Control Cable, non-plenum CRESNET-P: Cresnet® Control Cable, plenum

#### Notes:

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at <a href="https://www.crestron.com/salesreps">www.crestron.com/salesreps</a> or by calling 800-237-2041.

Specifications subject to change without notice. Crestron is not responsible for errors in typography or photography.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

3-Series, Cresnet, Crestron, and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. 3M and Dual Lock are either trademarks or registered trademarks of 3M Company in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. ©2012 Crestron Electronics, Inc.

# **C2N-IO** Control Port Expansion Module

