



VM-214DT

DA Conmutable 2 x 1:4 HDMI 4K60 4:2:0 y
Extensor de Rango HDBaseT con Ethernet,
RS-232, IR y Audio Estéreo

| HDMI | Ethernet - RJ-45 | HDCP Compliant
| HDBaseT | 4K/60 UHD (4:2:0)



El VM - 214DT es un distribuidor HDBaseT 4K a 60Hz (4: 2: 0) de alcance extendido y alta calidad que toma una entrada HDMI o HDBaseT de alcance extendido (seleccionable), ecualiza y vuelve a bloquear la señal y la distribuye a cuatro salidas HDBaseT de alcance extendido idénticas, junto con una señal de control de Ethernet, RS-232 e IR. La unidad también incluye una salida HDMI de bucle con desembeido (extracción) de audio a un puerto estéreo analógico. Como distribuidor extensor integrado, VM - 214DT re- extiende y distribuye señales HDBaseT nativas de alcance extendido con una resolución de video de hasta 4K

FEATURES

High Performance Extender Distributor - High-quality professional 1:4 distribution of native extended-reach HDBaseT signals, for deploying mid-way between an AV source and multiple remote displays and gaining extra extended-reach extension. It is coupled with both sides, input and output, extension of a maximum 4K@60Hz (4:2:0) 24bpp video resolution signal to maximum 100m (330ft) extended-reach over CAT copper cable, and even further reach for lower HD video resolution. The extender distributor is standard and capable of being connected to any market-available HDBaseT compliant extending product

Cables - For optimum range and performance, use recommended Kramer cables

HDMI Signal Extension - HDCP 1.4 compliant signal, supporting deep color, x.v.Color™, lip sync, 7.1 PCM, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0. EDID signals are passed through from the source to the display

I-EDIDPro™ Kramer Intelligent EDID Processing™ - An intelligent EDID handling, processing and pass-through algorithm that ensures Plug and Play operation for HDMI source and display systems

Looping HDMI Output - Enables monitoring and cascading to additional DAs

Ethernet Extension - Ethernet interface data flows in both directions, enabling extension of up to 100Mbps Ethernet connectivity for LAN communication and control of devices

Bidirectional RS-232 Extension - Serial interface data flows in both directions, enabling data transmission and control of devices

Bidirectional Infrared Extension - IR interface data flows in both directions, enabling remote control of peripheral devices located at either end of the extended line

Cost-effective Maintenance - Status LED indicators for HDMI and HDBT ports to facilitate easy local maintenance and troubleshooting. Remote IP device management via built-in web pages or RS-232 control connection. Local and remote firmware upgrade via mini-USB, control RS-232 or Ethernet connection and the K-Upload tool to ensure long field-proven deployment

Easy Installation - Twisted-pair cables for HDBaseT signals wiring. Rack mountable enclosure for mounting in a 1U rack space with included rack ears



TECHNICAL SPECIFICATIONS

Inputs	1 HDMI: On a female HDMI connector 1 HDBT: On an RJ-45 connector
Outputs	1 HDMI: On a female HDMI connector 4 HDBT: On RJ-45 connector 1 Unbalanced Stereo Audio: On a 3.5mm mini jack
Ports	1 IR: On a 3.5mm mini jack for IR link extension via HDBT outputs 1 RS-232: On a 3-pin terminal block for serial link extension via HDBT outputs 1 Mini USB: On a female USB connector for firmware upgrade 1 RS-232: On a 3-pin terminal block for device control 1 10/100BaseT Ethernet: On an RJ-45 female connector for device control via LAN and Ethernet link extension via HDBT outputs
Extension Line	4K @60Hz (4:2:0): Up to 100m (330ft) Full HD (1080p @60Hz 36bpp): Up to 130m (430ft) HDBaseT Ultra Mode and Full HD (1080p @60Hz 24bpp) Up to 180m (590ft) Compliance: HDBaseT 1.0
Video	Max. Resolution: 4K@60Hz (4:2:0) and 4K@30Hz (4:4:4) Compliance: Supports and HDCP 1.4 HDMI Support Deep color, x.v.Color™, lip sync, 7.1 PCM, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0
Analog Audio	Max Level: 1 Vrms THD + Noise: 0.03% @1kHz at nominal level
User Interface	Controls Input select, volume, and EDID read/select buttons. RS-232 device control, Ethernet, and DIP-switches Indicators Input select, EDID type, outputs and IR signal LEDs
Supported Web Browsers	Windows 7 and Higher – Internet Explorer (32/64 bit) version 10, Firefox version 30, Chrome version 35 MAC – Chrome version 35, Chrome version 63.0.3239.84, Firefox version 30, Firefox version 57.0.2, Safari version 7 Minimum Browser Window Size – 1024 x 768 when in full screen mode
Power	Consumption: 16VA Source: 100–240V AC, 50/60Hz
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: –40° to +70°C (–40° to 158°F) Humidity: 10% to 90%, RHL non-condensing
STANDARDS	Safety: CE

COMPLIANCE

Environmental: RoHs, WEEE

Enclosure

Size: 19" 1U

Type: Aluminum

Cooling: Fan Ventilation

Accessories

Included: Power power cord, rack ears

Product Dimensions

43.64cm x 18.30cm x 4.36cm (17.18" x 7.20" x 1.72") W, D, H

Product Weight

1.6kg (3.4lbs) approx

Shipping Dimensions

55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H

Shipping Weight

2.7kg (6.0lbs) approx

