

NEC MultiSync® ME651  
LCD 65" Message Essential Large Format Display

## Datasheet



### Your pathway to signage digitisation

Offering a professional feature set and NEC's renowned high reliability, yet at a very attractive price point, the NEC ME series presents the perfect opportunity to digitise your signage. Only commercial-grade displays are capable of delivering reliable, long-life performance and the ME Series presents lower budget business operators the upgrade path to professional digital signage without requiring specialist expertise.

Primed with an integrated USB MediaPlayer, the ME series offers out-of-the-box playback which can be easily upgraded thanks to NEC's modular approach. Enjoy all the flexibility you need to create, schedule and broadcast expert signage content, meaning your messaging is always fresh and up to date. Capable of landscape or portrait orientation and up to 18/7 hours continuous operation, local retailers, restaurants and small business enterprises can deliver dynamic advertising and infotainment to their customers whilst benefiting from the efficiencies gleaned through digitisation.

## Benefits

**Modern and slim design** – robust yet elegant allowing for an unobtrusive integration into any application and environment.

**Secure remote management** – control your devices remotely and securely using NEC NaviSet Administrator 2; proactively manage maintenance requirements saving time and resources

**Ease of use and operation** – smart installation, operation and maintenance functionality ensures accurate performance over the entire lifetime of the display saving time, effort and resources.

**Future Ready Connectivity** – featuring multiple industry standard digital and analogue signal inputs for flexible integration into AV infrastructures.

**Effortless content playback** – the integrated USB media player supports various image video file formats for effortless and standalone content playback.

## Product Information

|               |  |
|---------------|--|
| Product Name  | NEC MultiSync® ME651                           |
| Product Group | LCD 65" Message Essential Large Format Display |
| Order Code    | 60005062                                       |

## Display

|                           |   |
|---------------------------|---|
| Panel Technology          | IPS with Direct LED backlights                              |
| Screen Size [inch/cm]     | 65 / 163.9  |
| Aspect Ratio              | 16:9  |
| Brightness [cd/m²]        | 400   |
| Contrast Ratio            | ≥ 8000:1 <sup>1</sup>                                       |
| Viewing Angle [°]         | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |
| Colour Depth [bn]         | 1.073 (8bit + FRC)  |
| HDR                       | HDR10; HLG; PQ  |
| Response Time (typ.) [ms] | 6   |
| Panel Refresh Rate [Hz]   | 60  |
| Haze Level [%]            | Standard (1)  |
| Supported Orientation     | Landscape; Portrait   |

## Synchronisation Rate

|                            |          |
|----------------------------|----------|
| Horizontal Frequency [kHz] | 26 - 135 |
| Vertical Frequency [Hz]    | 23 - 86  |

## Resolution

|                       |   |  |  |   |
|-----------------------|---|--|--|---|
| Native Resolution     | 3840 x 2160   |  |  |   |
| Supported Resolutions | 1024 x 768;<br>1280 x 1024;<br>1280 x 720;<br>1360 x 768; | 1366 x 768;<br>1400 x 1050;<br>1440 x 900;<br>1600 x 1200; | 1650 x 1050;<br>1920 x 1080;<br>1920 x 1200;<br>1920 x 2160; | 2560 x 1440;<br>2560 x 1600;<br>3840 x 2160;<br>4096 x 2160 |

## Connectivity

|                       |  |
|-----------------------|--|
| Input Video Digital   | 1 x DisplayPort (with HDCP); 2 x HDMI (with HDCP)    |
| Input Audio Digital   | 1 x DisplayPort; 2 x HDMI                            |
| Input Control         | LAN 100Mbit; remote control wire (3,5mm jack); RS232 |
| Input Data            | 1 x USB 2.0 (MediaPlayer)                            |
| Output Audio Analogue | 1 x 3,5 mm jack                                      |
| Input Detect          | Custom; First; Last                                  |

## Open Modular Intelligence

|                     |   |
|---------------------|---|
| Intel® SDM          | accepts Intel® Smart Display Modules Large and Small up to 66 W |
| Compute Module Slot | RPi Compute Module 4  |

## Sensors

|                    |   |
|--------------------|---|
| Temperature Sensor | Integrated, 3 sensors, triggered actions programmable |
|--------------------|---|

## Electrical

|                                |                                |
|--------------------------------|--------------------------------|
| Power Consumption Eco/max. [W] | 165 shipping                   |
| Power Savings Mode [W]         | < 0.5; < 2 (Networked Standby) |

|                  |                                  |
|------------------|----------------------------------|
| Power Management | VESA DPMS                        |
| Power Supply     | 100-240 V AC; 50/60 Hz; internal |

## Environmental Conditions

|                            |           |
|----------------------------|-----------|
| Operating Temperature [°C] | +0 to +40 |
| Operating Humidity [%]     | 20 to 80  |
| Storage Humidity [%]       | 10 to 90  |
| Storage Temperature [°C]   | -20 to 60 |

## Mechanical

|                                       |                               |
|---------------------------------------|-------------------------------|
| Dimensions (W x H x D) [mm]           | 1,462.3 x 837.3 x 68.1        |
| Weight [kg]                           | 29.4                          |
| Bezel Width [mm]                      | 14.9                          |
| VESA Mounting [mm]                    | 4 holes; 400 x 400 (FDMI); M8 |
| Ingress Protection                    | IP5x (front); IP2x (back)     |
| Packaging Dimensions (W x H x D) [mm] | 1,736 x 1,033 x 280           |
| Packaging Weight [kg]                 | 41.7                          |
| Colour Bezel                          | Pantone 426M (black)          |
| Material                              | Metal                         |

## MediaPlayer

|                                      |   |
|--------------------------------------|---|
| Supported File Storage / File System | USB 2.0 / FAT16, FAT32  |
| Supported Image Formats              | JPG (baseline, progressive, RGB, CMYK); max. resolution 15360 x 8640  |
| Supported Video Formats              | MPG (MPEG1/2/4, max res 1080p@30Hz); MP4 (MPEG2/4, H.263, H.264, HEVC/H.265, max res 3840x2160@60Hz); TS (MPEG2, H.264, HEVC/H.265, max res 3840x2160@60Hz); audio: LPCM, MP3, AAC; WMV (video H.264, Windows Media Video 9, max res 1080p@30Hz, audio WMA 9, WMA 10 Pro) |
| Supported Audio Formats              | MP3 (MP3); max. bit-rate 320 kBit/s   |

## Available Options

|             |   |
|-------------|---|
| Accessories | Feet (ST-65M); MPI4 NEC MediaPlayer Kit; Presence Sensor (KT-RC3); Soundbar (active: SP-ASCM-IQ2 / SP-ASCM-2); Speaker (SP-RM3a); Trolley (PD04-Tipster Trolley); Wall mount (PDW S 32-65 L, PDW S 32-65 P) |
|-------------|---|

## Green Features

|                      |   |
|----------------------|---|
| Energy Efficiency    | Energy consumption: 156 kWh/1000 h; Energy efficiency class: G; LED backlight |
| Ecological Standards | EnergyStar 8.0  |

## Additional Features

|                         |   |
|-------------------------|---|
| Special Characteristics | DICOM Simulation; HDMI ARC; Powered USB Port (10 W); Removable Logo   |
| Safety and Ergonomics   | BSMI; CE; EAC; EMC Class B; Energy Star 8; FCC Class B; KC/KCC; PSB; RCM; RoHS; VCCI  |
| Pixel Failure Class     | ISO 9241-307, Class 1   |
| Audio                   | Integrated Speakers (10 W + 10 W)   |
| Shipping Content        | 2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual  |
| Warranty                | 3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension <sup>2</sup>                  |
| Operating Hours         | 18/7  |
| External Control        | AMX NetLinx Support; ASCII Control Commands; Crestron Connected; HDMI CEC; HTTP Browser; PJLink; Scheduled Timer; Scheduled Timer; SNMP |

|                    |  |
|--------------------|--|
| Remote Management  | Automated Email Alerts; NEC NaViSet Administrator 2                  |
| Security           | Disable HW Buttons; Disable IR Functionality; Emergency Notification |
| Resistance to Fire | Metal backcover, plastic material certified acc. to UL94-5VB         |

<sup>1</sup> out of the box conditions, local dimming ON

<sup>2</sup> please refer to terms and conditions of warranty extensions



RoHS



CE



FCC Class B



RCM



VCCI

This document is © 2022 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 26.12.2022