



WP-211T

Conmutador/transmisor automático de placa de pared HDMI 4K60 4:2:0 sobre PoE HDBaseT de largo alcance

| HDMI | Ethernet - RJ-45 | 4K/60 UHD (4:2:0)
| HDCP 2.2 Compatible



WP-211T es un conmutador automático de placa de pared alimentado por PoE de alto rendimiento de señales de video 4K HDMI, transmitidas a través de un enlace de extensión HDBaseT de largo alcance. Ofreciendo opciones de conmutación de prioridad y último conectado, cambia automáticamente de acuerdo con el esquema de conmutación seleccionado basado en la detección de señal de video activa

FEATURES

Plug & Play Auto Switcher - Wall or podium mountable switcher, easily accessible for plugging user device to any of its HDMI input connections, it auto-plays switched source signal on connected display according to user-configured preferences

Automatic Input Selection - Plug & play auto switching based on last connected input or manual selection

High Performance Switcher Transmitter - Professional HDBaseT Switcher transmitter for providing long-reach signals over twisted pair copper infrastructures. This switcher transmitter is a standard transmitter that can be connected to any market-available HDBaseT-compliant extension product

HDMI Signal Switching - HDMI 2.0 and HDCP 2.2 compliant, it supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D

Multi-channel Audio Switching - Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound

I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling, processing, locking and pass-through algorithm ensures Plug and Play operation for HDMI source and display systems

Reliable PoE (Power over Ethernet) Powering - Auto-senses the extension line PoE status, it accepts power from a remote PoE provider such as a PoE matrix, with optional mains powering from connected power adapter

Easy Installation - Compactly fits into standard US, EU and UK 1-gang in-wall box size, supporting decorative integration with room deployed user interfaces such as electrical switches. Wall-plate installation is fast and cost-effective via a single twisted pair cable, providing both video signal and power (PoE) connections



TECHNICAL SPECIFICATIONS

Inputs	2 HDMI: Con conectores hembras HDMI
Outputs	1 HDBaseT: Con un conector RJ-45
Video	Max. Velocidad de datos: 8.91Gbps (2.97Gbps por canal gráfico) Max. Resolución: 4K @ 60Hz (4: 2: 0) Cumplimiento de normativa: HDCP 2.2 (no admite la conversión a HDCP 1.4), HDMI 1.4
Extension Line	Up to 40m (130ft) At 4K@60Hz (4:2:0) Up to 70m (230ft) At full HD (1080p @60Hz 36bpp) : Note When using Kramer HDBaseT cables Compliance HDBaseT 1.0
User Interface	Controles: Botones del panel y últimos interruptores DIP conectados/prioritarios
Power	Source 5V DC PoE Acceptor Consumption 780mA Consumption with PoE 9 watt
Enclosure	Tamaño: 1 placa de pared de EE. UU., UE o Reino Unido Refrigeración: Ventilación por convección
CUMPLIMIENTO NORMATIVA:	EMC EN 55032; IEC 60950-1(ed.2); IEC 60950-1(ed.2)am1; IEC 60950-1(ed.2)am2
Environmental Conditions	Temperatura de funcionamiento: 0 ° a + 40 ° C (32 ° a 104 ° F) Temperatura de almacenamiento: -40 ° a + 70 ° C (-40 ° a 158 ° F) HUMEDAD: 10% a 90%, RHL sin condensación
Accessories	Todas las versiones incluyen: 1 adaptador de corriente, 1 cable de alimentación La versión US – D incluye: 2 juegos de marcos y placas frontales de EE. UU. (1 en negro y 1 en blanco) La versión europea incluye: 1 marco blanco de la UE, 1 marco blanco del Reino Unido, 1 placa frontal blanca de EU / UK
Product Dimensions	UK: 8.60cm x 3.80cm x 8.60cm (3.39" x 1.50" x 3.39") W, D, H EU: 8.00cm x 3.80cm x 8.00cm (3.15" x 1.50" x 3.15") W, D, H US: 6.98cm x 3.70cm x 11.43cm (2.75" x 1.46" x 4.50") W, D, H EU, UK: 8.00cm x 3.80cm x 8.00cm (3.15" x 1.50" x 3.15") W, D, H
Product Weight	UK: 0.2kg (0.4lbs) approx EU: 0.2kg (0.4lbs) approx US: 0.2kg (0.4lbs) approx

EU, UK: 0.2kg (0.4lbs) approx

Shipping Dimensions UK: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H

EU: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H

US: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H

EU, UK: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H

Shipping Weight UK: 0.6kg (1.2lbs) approx

EU: 0.6kg (1.2lbs) approx

US: 0.6kg (1.2lbs) approx

EU, UK: 0.6kg (1.2lbs) approx





CONFIGURATIONS

WP-211T/US(W/B)	US-D-size Wall-Plate Switcher/Transmitter with White & Black Decora® Design Frame Sets
WP-211T/EU-80/86(W)	EU & UK-size Wall-Plate Switcher/Transmitter with EU & UK White Frames

