

[Click to Print This Page](#)



E-VISION LASER 11000 4K-UHD DIGITAL PROJECTOR

THE VISIONARIES CHOICE




E-Vision Laser 11000 4K-UHD

9,500 ANSI / 10,500 ISO Lumens | Contrast Ratio: 6,000:1 (Dynamic Black) 1,000:1 native | Part Number: 120-602

Key Specifications:

Colour System:	Laser Phosphor with enhanced colourwheel
Display Type:	1 x 0.66" WQXGA+ TRP UHD DMD™
DMD Specification:	Display resolutions 4K-UHD (3840 x 2160) or WQXGA+ (2716 x 1528) 8.3 megapixels on screen at 4K-UHD Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16:9
Fill Factor	Not applicable: Smooth Picture DMD™
Key Features:	Video & Graphics Processing <ul style="list-style-type: none">• HDR processing• Two projectors in one - 4K-UHD and WQXGA+• DisplayPort 1.2 with HDCP 2.2• 2 x HDMI 2.0 with HDCP 2.2• 2 x HDMI 1.4b inputs with HDCP 1.4 for Dual Pipe processing and Frame Sequential 3D Format.• Sequential Processing: 3D via single HDMI 1.4b input• Dual Pipe Processing: 3D Left and Right Eyes via two HDMI 1.4b inputs• Synchronisation of active glasses• 3G-SDI with loop-through• DICOM simulation mode

	<p>Geometry Correction</p> <ul style="list-style-type: none">• Onboard 4-Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, Arc, and Image Rotation• User definable custom warp• Digital zoom, pan and scan.• Independent four boundary blanking control for custom input window sizing• Scaling available for fixed aspect ratio screens.• Unscaled processing for pixel mapped display. <p>Edge Blending</p> <ul style="list-style-type: none">• Blending control available for all sides with width control.• Correction for non-active pixels at the edge of the display. <p>Picture in Picture</p> <ul style="list-style-type: none">• Two sources can be displayed simultaneously using 2D inputs with the original aspect ratios maintained <p>HDBaseT® Interface</p> <ul style="list-style-type: none">• Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable• Allows projector to be placed up to 100m from source with low cost cabling• Supports up to 4K UHD 3840 x 2160@60Hz 4:2:0 or 4K UHD 3840 x 2160@30Hz 4:4:4 <p>Colour Processing</p> <ul style="list-style-type: none">• Four colour modes available: ColorMax / Manual Color Matching / Color Temperature / Gains and Lifts• Powerful seven point colour correction for accurate colour matching with presets• Easy colour temperature selection• Manual seven point colour adjustment• Traditional lifts and gains <p>Projector Controller Software</p> <ul style="list-style-type: none">• Intuitive user interface for network control• Simultaneous control of user-defined groups of projectors• At-a-glance monitoring of projector status <p>Projector Automation</p> <ul style="list-style-type: none">• Real-time clock provides daily on/off automation• E-mail alerts for system status
Source Compatibility	<p>2D graphics standards up to 4K-UHD 3840 x 2160 resolution at 60Hz via HDMI 2.0, HDBaseT (4:2:0) and DisplayPort inputs.</p> <p>3D graphics standards up to WQXGA at 120Hz DualPipe via HDMI 1.4b inputs.</p> <p>3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.</p> <p>WQXGA+ mode</p> <p>2D sources up to WQXGA+ at 120Hz can be displayed scaled to fit WQXGA+.</p> <p>3D sources up to WQXGA at 120Hz can be displayed scaled to fit WQXGA+.</p> <p>4K-UHD mode</p> <p>2D sources up to 4K-UHD will be displayed scaled to fit 4K-UHD.</p> <p>Auto mode</p> <p>Sources greater than WQXGA+ will be displayed scaled to fit 4K-UHD.</p> <p>Sources up to WQXGA+ will be displayed scaled to fit WQXGA+.</p>
Inputs/Outputs	

	Video & Computer			Communication & Control														
	Type	Connector	Qty	Type	Connector	Qty												
	DisplayPort 1.2 (2D)	DisplayPort	1	3D Sync Out	BNC	1 1 2 1 1 2 1												
	HDMI 1.4b (3D)	HDMI	2	3D Sync In	BNC													
	HDMI 2.0 (2D)	HDMI	2	LAN	RJ45													
	3G-SDI in (2D)	BNC	1	RS232	9-pin D													
	3G-SDI out	BNC	1	Wired Remote	Sub													
	HDBaseT (see LAN) (2D)	RJ45	1	12V Trigger	3.5mm													
				3D Sync IR Out	Stereo													
					Jack													
				3.5mm														
				Stereo														
				Jack														
				BNC														
3D Formats Supported	Frame Sequential Dual-Pipe																	
HDTV Formats Supported	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz, 100Hz, 120Hz) 1080i (50Hz, 60Hz) 720p (50, 60Hz) 2K (24Hz, 25Hz, 30Hz, 50Hz, 60Hz) 4K-UHD (24Hz, 25Hz, 30Hz, 50Hz, 60Hz)																	
Computer Compatibility	2D 4K-UHD up to 60Hz. WQXGA+ up to 120Hz. 3D Supported formats will be displayed within WQXGA+.																	
Bandwidth	498 megapixels per second via DisplayPort and HDMI 2.0.																	
Remote Control	Addressable IR remote control, wireless and wired. On-Board keypad																	
Automation Control	Crestron RoomView® Connected PJLink Class 1 LAN RS232 AMX (Device Discovery) Served web pages (projector status, projector control, Crestron RoomView®, network settings, alert mail setup, time setup, error log, On Screen Display)																	
Colour Temperature	3200K to 9300K																	
Operation																		
illumination Type	Laser Light Source																	
Typical illumination Life	20,000 hours																	
Lenses	<table><tr><th>Lens</th><th>Part No.</th><th>Optimised Focus Range*</th><th>Lens Shift (Frame)</th></tr><tr><td>0.38 :1 fixed</td><td>117-341</td><td>0.68m - 2.44m</td><td>Depends on image size, see Installation Guide.</td></tr><tr><td>0.74 - 0.93 :1 zoom</td><td>115-339</td><td>1.02m - 12.7m</td><td>Vert: 0.5 (U) 0.3 (D)</td></tr></table>						Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.38 :1 fixed	117-341	0.68m - 2.44m	Depends on image size, see Installation Guide.	0.74 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.5 (U) 0.3 (D)
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)															
0.38 :1 fixed	117-341	0.68m - 2.44m	Depends on image size, see Installation Guide.															
0.74 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.5 (U) 0.3 (D)															

				frame, Hor: 0.1(L) 0.2 (R) frame
	0.76 :1 fixed	112-499	0.81m - 5.08m	none
	1.24 - 1.78 :1 zoom	112-500	1.33m - 11.73m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
	1.71 - 2.25 :1 zoom	112-501	1.83m - 14.9m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
	2.2 - 3.67 :1 zoom	112-502	2.36m - 24.2m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
	3.54 - 5.36 :1 zoom	112-503	3.8m - 35.35m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
	5.24 - 8.27 :1 zoom	112-504	5.59m - 54.8m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,				
Lens Mount	Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).			
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet			
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes			
Power Requirements	100-130VAC and 200-240VAC selectable, 50/60Hz single phase			
Power Consumption	100V_60HZ Typical: 1344W, Maximum TBDW 240V_50HZ Typical: 1290W , Maximum TBDW			
Thermal Dissipation	Typical 4590 BTU/Hour @ 100VAC Typical 4406 BTU/Hour @ 240VAC			
Fan Noise	Smooth Picture On: Normal mode: typical 43 (max 45) dBA Eco mode: typical 39 (max 41) dBA Smooth Picture Off: Normal mode: typical 42 (max 44) dBA Eco mode: typical 38 (max 40) dBA			
Operating/Storage Temperature Operating:	Operating: 5 to 40C (41 to 104F) Storage: -10 to 60C (14 to 140F)			
Operating Humidity	10 to 85% non-condensing ((with maximum temperature of 40C)			
Weight	31 kg / 63.34 lbs			
Dimensions	L: 59.83 cm x W: 50 cm x H: 21.85 cm L: 23.55 in x W: 19.68 in x H: 8.60 in			

Safety & EMC Regulations	UL/cUL, BIS, CB, CCC, CQC Eco label, CECP, KC, KTL, IC,BSMI, RoHS (China), RoHS (EU),FCC Class A, FDA,CE, IEC EN 60825-1 Class 3R Laser Product, IEC EN 62471-5 Risk Group 2, WEEE (EU), PSE, UKCA	
Accessories	Accessory	Part No.
	Infrared Remote (replacement)	117-880
	<i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i>	
Downloads	PDF CAD Drawings AUTOCAD Drawings STEP / IGS Drawings Lens CAD Drawings	
User Guide	User Guides User Guides (German) Laser Risk Group Document Important Information Control Protocol Ultra Short Throw Lens Ultra Short Throw Lens Installation Guide	



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, LTD



Greenside Way, Middleton Manchester, UK

M24 1XX



T: +44.161.947.3300 | F: +44.161.684.7674



www.digitalprojection.co.uk

DIGITAL PROJECTION

A Delta Group Company

Specifications subject to change without notice.
 ©2022 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



Certificate Number 13629
 ISO 9001



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770