MAXHUB



Lightweight construction, whole column integration, easy installation

31mm, 6.5mm side frame, 6.5KG cabinet weight.





31mm thick

Weights 6.5kg

> Raptor Series - Ultra Wide

Aspect Ratio		21:9	
Product Model	LA132V11	LA181V11	LA209VII
Display Diagonal (inches)	132"	181"	209"
Pixel (mm)	1.27	1.58	19
Overall Dimension (WxHxD)(mm)	3064 × 1489 x 31	4284 × 1832 x 31	4894 × 2175 x 31
Weight (kg)	108	189	260
Resolution	2400 x 1080	2688 x 1080	2560 x 1080
Brightness (nits)	100-550cd/m²		
Refresh Rate (Hz)	3840		
Contrast	6500:l		
Audio Frequency	Built-in 2 *30W audio system, 2.0 channel, full frequency range		
Cabinet Material	Magnailum		
Viewing Angle (H/V)	160°/140°		
Input Port	3-way HDMI 2.0 4K@60Hz Signal Input		
Picture in picture	Support HDMI 2.0 signal Picture in Picture		
Installation Mode	Wall Mounting / Hanging / Mobile Stand	Wall Mo	unting / Hanging
Maintenance	Front Access		
Power Consumption (Max./Ave.)(KW)	1.84/0.63	2.38/0.81	2.98/1.01
Recommended Viewing Distance (m)	≥2.5	≥3.2	≥3.9













MAXHUB

Raptor Series-Ultra Wide

21:9 All-In-One Display Solution

MAXHUB

Raptor Series - Ultra Wide is MAXHUB's AlO solution of overall conference solution for Hybrid Signature rooms. The solution contains high definition LED display, which present the video images of speakers or attendees at the conference onsite.



High definition display on giant screen Stunning visual enjoyment

- 21:9 2400/2560/2688*1080P ultra HD resolution.
- High grey scale level under low brightness.
- Hyper Bit 16+4 Bit Processing, self-developed system with multi-stage correction technology.

Highly integrated design audio-visual integration

Professional speaker, 90 DB sensitivity, 180HZ-20KHZ frequency response, 2*30W power.



Professional speaker



90 DB sensitivity



180HZ-20KHZ frequency response



2*30W power





The device screen synchronizes the main LED screen supports a variety of screen mirroring method to achieve wonderful content sharing

One-click screen sharing saves lots of space and help gets rid of the shackles of cumbersome wires. Display content of Computer, mobile phone and tablet can be easily mirrored to the LED screen.

Industrial system, stable and reliable support the installation of a variety of common conference systems supporting peripheralunit, easy to carry out collaboration

- Highly integrated board, 3x stability.
- Be compatible with Microsoft Teams Front Row and Zoom room.
- Bundle with MAXHUB Wireless screensharing , Speakerphone, PTZ camera and MTR XCore kit.













Wireless screensharing

PTZ Camera

MAXHUB XC13T

MAXHUB TCP20T

MAXHUB UC BM35

Centralized control management Support remote management

Built-in RS232 port, easy to achieve device interconnection, support self-developed operation and maintenance system, unified management, reduce stand-by power consumption and content publishing. Support remote maintenance dehumidification, screen inspection, abnormal warning and factory recovery.