



**niveo**||  
P R O F E S S I O N A L



**N10GMM, (850 nm Multimode XFP 10G (MM, GBIC))**  
10GFC 1200-MX-SN-I(Fiber Channel), 10GBASE-SR(Ethernet)

More information:

[WWW.NIVEOPROFESSIONAL.COM](http://WWW.NIVEOPROFESSIONAL.COM)

[INFO@NIVEOPROFESSIONAL.COM](mailto:INFO@NIVEOPROFESSIONAL.COM)



# Product Specification

## Features

- Multi Mode 10G Fiber Module
- Compliant with 10GFC-1200MX-SN-I Fiber Channel Standard
- Compliant with IEEE802.3ae 10GBASE SW/SR Ethernet Standard
- Compliant with XFP MSA INF-80771
- Differential CML inputs and CML outputs
- Differential PECL reference clock input (1/64 transmitter data)
- Single Power supply 3.3V
- TTL signal detect indicator
- Hot Pluggable
- Class 1 laser product complies with EN 60825-1

## Absolute Maximum Ratings

PARAMETER	SYMBOL	MIN	MAX	UNITS	NOTE
Storage Temperature	$T_s$	-40	85	°C	
Supply Voltage	$V_{cc3}$	-0.5	4.0	V	
Input Voltage	$V_{IN}$	-0.5	$V_{cc}$	V	

## Recommended Operating Conditions

PARAMETER	SYMBOL	MIN	MAX	UNITS	NOTE
Case operating Temperature	$T_c$	-10	70	°C	
Supply Voltage	$V_{cc3}$	3.1	3.5	V	
Supply Current	$I_{cc3}$	---	400	mA	



## Transmitter Electro-optical Characteristics

$V_{cc} = 3.1 \text{ V to } 3.5 \text{ V}$ ,  $T_c = -10 \text{ }^\circ\text{C to } 70 \text{ }^\circ\text{C}$

PARAMETER	SYMBOL	MIN	TYP.	MAX	UNITS	NOTE
Operating Data Rate			9.95/ 10.51875		Gbps	
Input Reference Clock Rate			1/64 Operating Data Rate			
Output Optical Power (50/125 $\mu\text{m}$ fiber, NA=0.20) (62.5/125 $\mu\text{m}$ fiber, NA=0.275)	$P_{out}$	-7.1	---	-1	dBm	
Optical Modulation Amplitude (OMA)	$OMA$	---	---	---	dBm	Refer to IEEE 802.3ae Table 52-3
Extinction Ratio	$ER$	3			dB	
Center Wavelength	$\lambda_c$	840		860	nm	
Spectral Width (RMS)	$\Delta\lambda$	---	---	---	nm	Refer to IEEE 802.3ae Table 52-8
Relative Intensity Noise	$RIN$	---	---	-128	dB/Hz	
Output Eye			Compliant with IEEE802.3ae			
Differential Input Voltage	$V_{DIFF}$	0.25	---	1.0	V	
TX_DISABLE Assert Time	$t_{off}$	---	---	10	$\mu\text{s}$	
TX_DISABLE Negate Time	$t_{on}$	---	---	2	ms	
Time to initialize	$t_{init}$	---	---	300	ms	
nterrupt assert delay	$\overline{\text{nterrupt\_on}}$	---	---	200	ms	



## Receiver Electro-optical Characteristics

$V_{CC} = 3.1 \text{ V to } 3.5 \text{ V}$ ,  $T_C = -10^\circ\text{C to } 70^\circ\text{C}$

PARAMETER	SYMBOL	MIN	TYP.	MAX	UNITS	NOTE
Optical Input Power-maximum	$P_{IN}$	-1	---	---	dBm	BER < $10^{-12}$
Receiver Sensitivity	$P_{IN}$	---	---	-9.9	dBm	BER < $10^{-12}$
Receiver Sensitivity in OMA	$P_{IN}$	---	---	-11.1	dBm	BER < $10^{-12}$
Operating Center Wavelength	$\lambda_C$	840	---	860	nm	
Optical Return Loss	$ORL$	12	---	---	dB	
Loss of Signal-Asserted	$P_A$	---	---	-20	dBm	
Loss of Signal-Deasserted	$P_D$	-12	---	---	dBm	
Differential Output Voltage	$V_{DIFF}$	0.575	---	0.725	V	
TTL Input High Voltage		2		$V_{CC}$	V	
TTL Input Low Voltage		0		0.8	V	
TTL Output High Voltage		2.4	---	$V_{CC}$	V	
TTL Output Low Voltage		0	---	0.4	V	
Receiver Loss of Signal Assert Time (off to on)	$t_{A,RX\_LOS}$	---	---	100	$\mu\text{s}$	
Receiver Loss of Signal Assert Time (on to off)	$t_{D,RX\_LOS}$	---	---	100	$\mu\text{s}$	
I2C Clock Frequency				400	$\text{kHz}$	