



APC Smart-UPS On-Line, 1500VA, Rackmount 2U, 120V, 6x NEMA 5-15R outlets, SmartSlot, Extended runtime, W/ rail kit

SRT1500RMXLA

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main

Main	
Main Input Voltage	120 V
Product or Component Type	Uninterruptible power supply (UPS)
Main Output Voltage	120 V
Kw Rating	1350 W
Rated power in VA	1500 VA
Input Connection Type	NEMA 5-15P
output connection type	6 NEMA 5-15R
Number of rack unit	2U
Cable length	6 ft (1.8 m)
Number of cables	1
Provided equipment	CD with software Documentation CD Installation guide Rack mounting hardware Rack Mounting brackets Rack Mounting support rails USB cable Warranty card
Range of Product	Smart-UPS On-Line

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery Type	Lead-Acid battery
Battery Voltage	48V
Extendable Run Time	1
Included Battery Modules	1
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Battery life	35 year(s)

Replacement battery	APCRBC155 ☐
Battery Charge Power (Watts)	91 W rated

General

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	High density
Redundant	No
Topology	Double Conversion Online

Physical

•	
color	Black
Height	3.35 in (8.5 cm)
Width	17.01 in (43.2 cm)
Depth	20.00 in (50.8 cm)
Product Weight	48.5 lb(US) (22 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal

Input

Efficiency at full load	90150 V
Input Frequency	47 - 70 Hz auto-sensing

Output

Bypass type	Built-in Bypass
Crest factor	3:1
Harmonic distortion	Less than 2%
Maximum configurable power in VA	1500 VA
Max Configurable Power (Watts)	1350 W
Wave type	Sine wave
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications	ENERGY STAR V2.0 (USA)
------------------------	------------------------

Environmental

Acoustic level	50 dBA
Online Thermal Dissipation	463 Btu/h

Operating altitude	010000 ft
Ambient air temperature for operation	32104 °F (040 °C)
Ambient Air Temperature for Storage	-4122 °F (-2050 °C)
Storage altitude	050000 ft (0.000000000015240.0000000000 m)
IP degree of protection	IP20
Relative Humidity	095 % non-condensing
Storage Relative Humidity	095 % non-condensing

Communications & Management

Emergency Power Off (EPO)	Yes
Free slots	1
Alarm	Audible and visible alarms : prioritized by severity

Surge Protection and Filtering

Surge energy rating 480 .

Ordering and shipping details

GTIN 731304330073

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.65 in (24.5 cm)
Package 1 Width	27.17 in (69.0 cm)
Package 1 Length	23.43 in (59.5 cm)
Package 1 Weight	71.83 lb(US) (32.58 kg)

Contractual warranty

Warranty 3 years repair or replace (excluding battery) and 2 years for battery



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

☑ Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	2584	
Environmental Disclosure	Product Environmental Profile	

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
[™] Energy efficiency	
Optimized Energy Efficiency	Energy efficient product
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes