
MAXHUB Raptor Series V3

DvLED All-In-One Display

Introducing the next generation Raptor Series V3 - the perfect solution for all your display needs. With its integrated slim design, this product seamlessly fits into any environment. It features an Android 13.0 system, multiple built-in Android applications, and a high-performance processor. Enjoy wireless screen sharing, switchable launcher templates, keypad lock function, six high-performance speakers, and an optional expandable built-in PC. It supports MAXHUB Pivot for centralized management and is compatible with various video conferencing software and MAXHUB MTR certified products. Elevate your display experience with our versatile DvLED All-in-One display.





Dual System

Built-in Android 13 system & Optional Windows PC



Convenient Device Control

Control via MAXHUB Touch Console or through application on mobile devices



Wireless Screen Sharing

Via MAXHUB Share/dongles,
Miracast, Chromecast or AirPlay




BYOM

Use your own device with the hardware already in the meeting room



Immersive Audio System

4 full-range speakers +
2 low-frequency speakers
Maximum output power 120W



Abundant I/O Ports

Lots of A/V I/O connectivity options for external devices



Supports MAXHUB Pivot

Remote Managemant with MAXHUB Product Family



One-stop Solution for Large Space

Bundle with other MAXHUB Products to enhance the meeting experience.

Raptor Series V3


Model	LX120V07	LX138V07	LX150V07	LX165V07	LX180V07	LX220V07	LX220V18
Physical Specification							
LED Type	SMD	SMD	SMD	SMD	SMD	SMD	SMD
Size	120"	138"	150"	165"	180"	220"	220"
Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9	16:9
Pixel Pitch (mm/in)	1.3 / 0.051	1.5/ 0.059	1.7/ 0.067	1.9/ 0.074	2/0.079	2.5/ 0.047	1.2/0.047
Resolution	1920 × 1080	1920 × 1080	1920 × 1080	1920 × 1080	1920 × 1080	1920 × 1080	3840 × 2160
Overall Size (W*H) (mm/in)	2694 × 1624/ 106.1 × 63.9	3080 × 1840/ 121.3 × 72.4	3360 × 1998/ 132.3 × 78.7	3690 × 2183/ 145.3 × 85.9	4026 × 2373/ 158.5 × 93.4	4910 × 2869/ 193.3 × 112.9	4910 × 2869/ 193.3 × 112.9
Display Area (W*H) (mm/in)	2664 × 1499/ 104.9 × 59	3050 × 1715/ 120.1 × 67.5	3330 × 1873/ 131.1 × 73.7	3660 × 2058/ 144.1 × 81	3996 × 2248/ 157.3 × 88.5	4880 × 2744/ 192.1 × 108	4880 × 2744/ 192.1 × 108
Screen Thickness (mm/in)	28/1.1	28/1.1	28/1.1	28/1.1	28/1.1	28/1.1	28/1.1
Net Weight (Wall-mounting bar and stand not included) (kg/lb)	87/ 191.8	122/ 268.9	131/ 288.8	172/ 379.2	185/407.9	296/652.6	296/652.6
Gross Weight (Including Wall-mounting bar) (kg/lb)	165/ 363.7	287/ 632.7	311/ 685.6	350/756.2	375/826.7	515/1135.4	515/1135.4
Recommended Viewing Distance (m/ft)	≥ 2.8/ 9.19	≥ 3.2/ 10.5	≥ 3.4/ 11.15	≥ 3.8/ 12.47	≥ 4/ 13.12	≥ 5/ 16.4	≥ 5/ 16.4
Maintenance Mode	Front Access	Front Access	Front Access	Front Access	Front Access	Front Access	Front Access
Installation Options	Mobile Stand, Wall-mounting	Mobile Stand, Wall-mounting	Mobile Stand, Wall-mounting	Mobile Stand, Wall-mounting	Wall-mounting	Wall-mounting	Wall-mounting
Screen and Module Dimension (Wooden Box) (W*H*D) (mm/in)	1 pc: 1680 × 810 × 915/ 66.1 × 31.9 × 36	1 pc: 1900 × 760 × 1215/ 74.8 × 29.9 × 47.8	1 pc: 2170 × 680 × 1255/ 85.4 × 26.8 × 49.4	1 pc: 1500 × 1250 × 1230/ 59.1 × 49.2 × 48.4	1 pc: 1310 × 1330 × 930/ 51.6 × 52.4 × 36.6 1 pc: 1170 × 770 × 875/ 46.1 × 30.3 × 34.4	1 pc: 1560 × 1280 × 890/ 61.4 × 50.4 × 35 1 pc: 1560 × 1240 × 1070/ 61.4 × 48.8 × 42.1	1 pc: 1560 × 1280 × 890/ 61.4 × 50.4 × 35 1 pc: 1560 × 1240 × 1070/ 61.4 × 48.8 × 42.1
Lower Frame and Wall-mounting Bar Packing Dimension (Wooden box) (W*H*D) (mm/in)	1 pc: 2135 × 562 × 509/ 84.1 × 22.1 × 20	1 pc: 2064 × 556 × 497/ 81.3 × 21.9 × 19.6	1 pc: 2135 × 562 × 509/ 84.1 × 22.1 × 20	1 pc: 2064 × 556 × 497/ 81.3 × 21.9 × 19.6	1 pc: 2135 × 562 × 509/ 84.1 × 22.1 × 20	1 pc: 2064 × 556 × 497/ 81.3 × 21.9 × 19.6	1 pc: 2064 × 556 × 497/ 81.3 × 21.9 × 19.6

Electrical Parameter							
Operation Voltage	100~240VAC, 50/60Hz						
Standby Power	≤0.5W	≤0.5W	≤0.5 W	≤0.5W	≤0.5W	≤0.5W	≤0.5W
Average Power Consumption of Overall Unit	0.483 KW	0.447 KW	0.575 KW	0.731 KW	0.78 KW	1.101 KW	1.514 KW
Maximum Power Consumption of Overall Unit	1.611 KW	1.491 KW	1.916 KW	2.438 KW	2.6 KW	3.67 KW	5.046 KW
Number of 100-120V: Power Cable 200-240V:	1 1	1 1	2	2	2	2	2

Optical Specification	
Brightness	100~600 nits (Adjustable)
Refresh Rate	3840 Hz
Gray Scale	13~16 bit
	6500:1
Color Temperature	2300~9300K (Adjustable)
Viewing Angle	160° (H) / 140° (V)
LED Lifespan	≥100,000 hrs


Raptor Series V3

Buiilt-in Interface




Forward Facing

NO.	Description
1	Light Sensor (intelligent space sensing, allowing for automatic brightness adjustment)
2	IR
3	Type C
4	USB 3.0
5	USB 3.0
6	Menu Button (including brightness, color temperature, contrast, sound, signal source and other sub-menus)
7	Bright/OK (1.When the menu is Not called up, it is the brightness adjustment button, and the + and - keys are used to adjust the brightness; 2.When the menu is called up, it is used as confirm button.)
8	 In the brightness adjustment mode, it is the brightness reduction key; When the Menu is called up, it is the left/down/minus key The default is the volume down button
9	 In the brightness adjustment mode, it is the brightness increase key; When the menu Is called up, It is the right/up/Add key; The default is the volume up button.
10	Standby/Wake up button, dual-color indicator light (red/blue)



Downward Facing



Internal

NO.	Description
11	HDMI Input (HDMI 1.4)
12	HDMI Input (HDMI 1.4)
13	HDMI Output (HDMI 2.0)
14	3.5mm Audio Output
15	3.5mm Audio Input
16	USB Out (The computer can access to USB devices connected to panel,when connected to the Raptor through HDMI input and USB out at the same time)
17	3.5mm Audio Output
18	HDMI Input (HDMI 2.0, supports CEC)
19	HDMI Input (HDMI 1.4)
20	USB 2.0
21	RJ45 (Support RS232 Protocal)
22	RJ45 (with POE+ up to 30W, for Connection with MAXHUB PTZ Camera)
23	RJ45 OPS LAN
24	RJ45 Android LAN

Raptor Series V3

Audio	
Speaker Unit	4 full range units + 2 low frequency units
Speaker Max. Power	120W
Max. Sound Pressure Level	95 dB
System Parameter	
Operating System	Android 13.0
CPU	Four Cortex-A76+ four Cortex-A55, frequency 2.4GHz
RAM	8GB
Storage	64GB
Media Format	Support mainstream video format such as MPEG-1, MPEG-2, MPEG-4, H.263, H.264, H.265, VC-1, VP9, VP8, MVC, AV1; Support audio formats such as MP3; Support JPG, JPEG, BMP, PNG, GIF and other image format.
Bluetooth	5.3
Wi-Fi	WiFi 6, AP and STA modes, and WiFi 6 dual-band 2.4G/5G are available

Accessories	
Remote Control	1
Front Maintenance Tool	1
Tool kit	1
Wall-mounting Bar	1
Stand (optional)	ST90/ST92
Radar Touch Module (optional)	LID01A
PC Module (optional)	LMT71A

Environmental Parameter	
Operation Temperature	-10°C~40°C
Operation Humidity	10%~80%RH No condensation

Statement

Should the above-mentioned change in the document become necessary, the document may be updated without written notice.

Size and weight vary by configuration and manufacturing process, please refer to the actual product.

The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product.

The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance.

MAXHUB

Where Inspiration Moves Ahead.







