

Product: <u>8412</u> 🖄

Microphone Cable, 2 C #20 Str TC, Rayon & 85% TC Braid, Cotton Serve, EPDM Jkt

Product Description

Microphone Cable, 2 Conductor 20 AWG (26 x 34) Tinned Copper (High conductivity), EPDM Insulation, Rayon® Braid, 85% Tinned Copper Braid Shield, Cotton Serve, EPDM Jacket

Technical Specifications

Product Overview

| Construction Details Conductor Element No. of Elements Size Stranding Material Conductor(s) 2 20 AWG 26x34 TC - Tinned Copper (High Conductivity) Insulation Element Material Nom. Thickness Nom. Insulation Diameter Color Code Conductor(s) EPDM - Ethylene Propylene Diene Monomer 0.023 in (0.58 mm) 0.083 in (2.1 mm) White, Black | - Todaot o | | | | | | | | |
|---|---------------------------|-----------------|-----------|--------------|---|--------------------------|--------------|--|--|
| Conductor No. of Elements Size Stranding Material Conductor(s) 2 20 AWG 26x34 TC - Tinned Copper (High Conductivity) Insulation Image: Conductor(s) Element Material Nom. Thickness Nom. Insulation Diameter Color Code Conductor(s) EPDM - Ethylene Propylene Diene Monuter 0.023 in (0.58 mm) 0.083 in (2.1 mm) White, Black | Suitable Applications: Ri | | | | Ruggedized, deployable microphone for studio or live performance; Balanced analog audio | | | | |
| Element No. of Elements Size Stranding Material Conductor(s) 2 20 AWG 26x34 TC - Tinned Copper (High Conductivity) nsulation Element Material Nom. Thickness Nom. Insulation Diameter Color Code Conductor(s) EPDM - Ethylene Propylene Diene Monte 0.023 in (0.58 mm) 0.083 in (2.1 mm) White, Black | Construction Details | | | | | | | | |
| Element No. of Elements Size Stranding Material Conductor(s) 2 20 AWG 26x34 TC - Tinned Copper (High Conductivity) nsulation Element Material Nom. Thickness Nom. Insulation Diameter Color Code Conductor(s) EPDM - Ethylene Propylene Diene Monte 0.023 in (0.58 mm) 0.083 in (2.1 mm) White, Black | Conductor | | | | | | | | |
| Insulation Nom. Thickness Nom. Insulation Diameter Color Code Conductor(s) EPDM - Ethylene Propylene Diene Monomer 0.023 in (0.58 mm) 0.083 in (2.1 mm) White, Black | | No. of Elements | Size | Stranding | Material | | | | |
| Element Material Nom. Thickness Nom. Insulation Diameter Color Code Conductor(s) EPDM - Ethylene Propylene Diene Monomer 0.023 in (0.58 mm) 0.083 in (2.1 mm) White, Black | Conductor(s) | 2 | 20 AWG | 26x34 T | C - Tinned Copper (Hig | gh Conductivity) | | | |
| Element Material Nom. Thickness Nom. Insulation Diameter Color Code Conductor(s) EPDM - Ethylene Propylene Diene Monomer 0.023 in (0.58 mm) 0.083 in (2.1 mm) White, Black | Insulation | | | | | | | | |
| Duter Shield | Element | | Material | | Nom. Thickness | Nom. Insulation Diameter | Color Code | | |
| | Conductor(s) | EPDM - Ethylene | Propylene | Diene Monome | er 0.023 in (0.58 mm) | 0.083 in (2.1 mm) | White, Black | | |
| | . , | EPDM - Ethylene | Propylene | Diene Monome | er 0.023 in (0.58 mm) | 0.083 in (2.1 mm) | White, Black | | |
| Shield Type Material Coverage | Shield Type | Material | Covera | age | | | | | |
| Braid Rayon® 85% | | | _ | | | | | | |

Outer Jacket

Braid

| Separator | Material | Nom. Thickness | Nom. Diameter |
|--------------------------------------|---------------------------------------|------------------------|--------------------|
| Cotton Serve | EPDM - Ethylene Propylene Diene Monor | ner 0.035 in (0.89 mm) | 0.262 in (6.65 mm) |
| Overall Cable Diameter (Nominal): 0. | | 0.262 in (6.65 mm) | |

Electrical Characteristics

Tinned Copper (TC) 85%

Electricals

| Element | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Nom. Characteristic Impedence | Max. Current |
|--------------|-----------------------|-------------------------------|---|-------------------------------|-----------------------------|
| Conductor(s) | 10.6 Ohm/1000ft | 33 pF/ft (110 pF/m) | 58 pF/ft (190 pF/m) | 67 Ohm | 4 Amps per conductor @ 25°C |

Voltage

| Voltage Rating |
|----------------|
| 600 V |

Mechanical Characteristics

Temperature

Operating -50°C to +90°C

Bend Radius

Stationary Min. Installation Min.

| 2.6 in (66 mm) 2.6 in (66 mm) | | | | |
|---|--|--|--|--|
| Max. Pull Tension: | 100 lbs (45 kg) | | | |
| Bulk Cable Weight: | 14 lbs/1000ft | | | |
| | | | | |
| Standards and Compliance | | | | |
| Standards and Compliance Environmental Suitability: | Indoor (Not Riser or Plenum), Indoor | | | |
| | Indoor (Not Riser or Plenum), Indoor EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) | | | |
| Environmental Suitability: | | | | |

History

Update and Revision:

Revision Number: 0.522 Revision Date: 02-03-2025

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC | Footnote |
|---------------|-------------|------------|----------|--------------|----------|
| 8412 010100 | Black | Reel | 100 ft | 612825206361 | |
| 8412 010250 | Black | Reel | 250 ft | 612825206385 | |
| 8412 010500 | Black | Reel | 500 ft | 612825206330 | С |
| 8412 010U500 | Black | UnReel | 500 ft | 612825396987 | |
| 8412 0101000 | Black | Reel | 1,000 ft | 612825206378 | С |
| 8412 010U1000 | Black | UnReel | 1,000 ft | 612825206347 | |
| 8412 0061000 | Blue, Light | Reel | 1,000 ft | 612825206354 | С |
| 8412 0021000 | Red | Reel | 1,000 ft | 612825206316 | С |
| 8412 0041000 | Yellow | Reel | 1,000 ft | 612825206323 | С |

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.