



VS-211H2

Selector Automático de HDMI 2x1 4K HDR
HDCP 2.2

| HDMI | HDCP Compliant | 4K/60 UHD (4:2:0)
| 4K/60 UHD (4:4:4) | HDCP 2.2 Compatible



VS - 211H2 es un conmutador automático de alto rendimiento para señales de video HDMI 4K @ 60Hz (4: 4: 4). Al ofrecer opciones de esquema de conmutación automática de prioridad y última conexión, cambia automáticamente las señales de entrada a la conexión de salida, de acuerdo con el esquema de conmutación seleccionado y en función de la detección de señales de vídeo activas

FEATURES

HDMI Signal Switching - HDR and HDCP 2.2 compliant, it supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0

Multi-channel Audio Switching - Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound

I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling, processing, locking and pass-through algorithm ensures Plug and Play operation for HDMI source and display systems

Cost-Effective Maintenance - Status LED indicators for HDMI ports facilitate easy local troubleshooting

Easy Installation - Compact DigiTOOLS® fan-less enclosure fits for convenient under tables or dropped-ceiling mounting, or side-by-side mounting of 3 units in a 1U rack space with the recommended rack adapter



TECHNICAL SPECIFICATIONS

Inputs	2 HDMI En conectores HDMI hembra
Outputs	1 HDMI En un conector HDMI hembra
Ports	2 Contact-Closure Switches On a 3-pin terminal block connector for remote device operation
Video	Max. Transferencia de Datos 17.82GBPS (5.94Gbps por canal gráfico) Máx. Resolución 4K@60Hz (4:4:4) HDMI Support Deep Color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0 COMPATIBLE CON LOS ESTÁNDARES: HDR10, HDCP 2.2 (no admite la conversión a HDCP 1.4)
User Interface	CONTROLES: DIP-Switches estado/prioridad, control remoto cierre por contacto
NORMATIVA REGULADORA	Certificación EMC EN 55032, IEC 60950-1(ed.2), IEC 60950-1(ed.2)am1, IEC 60950-1(ed.2)am2
Environmental Conditions	Temperatura de funcionamiento 0° a +40°C (32° a 104°F) Temperatura de almacenamiento -40° a +70°C (-40° a 158°F) Humedad 10% a 90%, RHL sin condensación
Power	Consumo 5 V CC, 560 mA
Accessories	Incluido Adaptador de corriente
Product Dimensions	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
Product Weight	0.2kg (0.4lbs) approx
Shipping Dimensions	49.00cm x 18.60cm x 58.80cm (19.29" x 7.32" x 23.15") W, D, H
Shipping Weight	0.6kg (1.4lbs) approx



