

## PS-5D-20TL Technical Specifications

### 5V DC Power Supply for ASW-WP

Rev. 130703

The Intelix PS-5D-20TL power supply is a 5V DC power supply designed for use with Intelix ASW-WP wall plate extender. The tinned leads are to ensure a secure power connection with the extender's DC input terminal block. The power supply features US-style AC prongs.

Technical Specifications	
<b>I/O Connections</b>	
AC Connection	US AC prongs
DC Connection	Two (2) tinned leads
<b>Chassis and Environmental</b>	
Enclosure	Black ABS plastic
Dimensions (without AC adapter)	83 mm x 43 mm x 39 mm (3.27 in. x 1.69 in. x 1.54 in.)
DC Cable Length	120 cm ± 20 cm (47.25 in ± 7.875 in.)
Shipping Weight	0.21 kg (0.46 lbs)
Operating Temperature (Environment)	0° to +40° C (+32° to +104° F)
Operating Humidity (Environment)	20% to 90%, Non-condensing
Storage Temperature (Environment)	-10° to +60° C (+14° to +140° F)
<b>Power and Regulatory</b>	
Input Power	110-240V AC, 50/60 Hz, 0.5 A
Output Power	5V DC, 2 A
Regulatory	RoHS, FCC, CE, UL, GS
<b>Other</b>	
Standard Warranty	2 Years
Compatible Products	ASW-WP