OC525B-70V

5.25" 2-Way 70Volt, Indoor/Outdoor Dual Purpose, Loudspeaker

The OC525 Indoor/Outdoor speaker is the perfect choice for either main listening or sound reinforcement applications. It also makes a great choice when used as satellite speakers. It is provided with a 70Volt input with a 30 watt tap.

The 5.25" graphite mica filled polypropylene woofer cone and butyl rubber surround are virtually impervious to weather and insects. The 5/8" polycarbonate tweeter delivers clear crisp high frequencies to provide high performance and high fidelity sound in a small package.

This speaker color is offered in both white and black. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations. The perforated powder-coated aluminum alloy grill is long-lasting, corrosion resistant and rust-free.

Included in the package is a universal heavy gauge mounting kit. The kit includes a rust proof U bracket and large easy to install positive locking serrated knobs. The knobs are attached to the matching serrated area on the zero balanced point of the enclosure via threaded studs. This allows the speaker to easily be positioned to place the sound where you want it. Hand tightening will clamp the speaker in place. The speaker may be mounted either horizontally or vertically.

With our limited 5 year warranty you are assured years of superior trouble free operation.



SPECIFICATIONS	
Driver	5.25" Mica Filled Polypropylene Cone with Butyl Rubber Surround
Tweeter	5/8" (13mm) Polycarbonate Dome
Grill Specification	Perforated aluminum
Frequency Response	52Hz – 20kHz
Power Handling 70Volts	Single Tap 30 Watts @ 70Volts
SPL	89 dB 1W/1m
Height X Width X Depth	7 5/16 (185mm) x 6 ½ (165mm) x 9 7/8 (249 mm)







Part Number 93206

Manual URL www.currentaudio.com

Accessories Volume Control ZL75RWIA

