# **General Description**

The Shure UA221 is a bi-directional splitter/combiner which can be used to route the RF signal from a single antenna to two inputs, or to connect two antennas to a single input. The UA221 Antenna Splitter/Combiner Kit includes:

- (2) Single-input, dual-output passive antenna splitters
- (4) Coaxial cables
- (2) BNC male-to-male adapters
- (2) BNC bulkhead adapters


UA221 splitters are intended for use with Shure Wireless Systems. Use Shure  $\frac{1}{2}$ -wave or directional antennas and Shure 50  $\Omega$  low-loss antenna cables when configuring the wireless system.

Model	Frequency Range	Pass DC/Block DC
UA221	10-1000 MHz	Block
UA221-C-J	10-1000 MHz	Pass
UA221Z	1000-2000 MHz	Block
UA221Z-C-J	1000-2000 MHz	Pass


# **Installing the UA221 Splitters**

Use two UA221 Splitters and the supplied BNC male-to-male adapters and coaxial cables to split the RF signal from a single pair of antennas to the antenna inputs of two receivers.

Note: Antennas must be compatible with the operating frequency range of the receiver.



In this configuration, use UA221 or UA221Z, or ensure the receiver's DC bias is disabled.



When using powered antennas, use UA221-C-J or UA221Z-C-J.

# **Specifications**

### Frequency Range

UA221/UA221-C-J	10 MHz-1000 MHz
UA221Z/UA221Z-C-J	1000 MHz-2000 MHz

### Voltage Standing Wave Ratio (VSWR)

2:0

#### Impedance

50 Ω

#### **Isolation**

20 dB

#### **Insertion Loss**

2 dB (3 dB splitter loss not included)

#### **Dimensions**

 $64 \times 48 \times 22 \text{ mm} (H \times W \times D)$ 

#### Weight

45.3 g (1.6oz.)

## **Furnished Accessories**

## **Furnished Parts**

0.5 m (2 ft.) Coaxial Antenna Cable (4)	UA802
BNC Bulkhead Adapters, lockwasher, nut (2)	95A8647
BNC Male-to-Male Adapter (2)	95A8738